

# Energy Efficiency Ratings in Steel Doors

		1/2" Clear	1/2" Std Low-E	1/2" Clear GBG	1/2" Std Low-E GBG	1" Clear	1" Std Low-E	1" Std Low-E GBG	BBG Clear (Raised)	BBG Low-E (Raised)	BBG Clear (Lowered)	1" Decorative	Impact Clear	Impact Std Low-E	Impact GBG Std Low-E	Impact Decorative	1" Protector Clear	1" Protector CL-GBG	1" Protector Std Low-E	1" Protector Low-E-GBG
<b>Half Light</b> 36" & 3/4 Oval	U-Factor	0.25	0.23	0.25	0.23	0.24	0.21	0.21	0.26	0.23	0.22	0.22	0.23	0.21	0.21	0.21	0.24	0.24	0.22	0.22
	SHGC	0.17	0.14	0.16	0.13	0.17	0.14	0.13	0.17	0.14	0.06	0.12	0.14	0.13	0.11	0.11	0.15	0.14	0.14	0.13
	DT/VT	0.17	0.15	0.16	0.14	0.17	0.15	0.14	0.17	0.16	-	0.13	0.16	0.15	0.13	0.12	0.17	0.15	0.15	0.14
<b>3/4 Light</b> 48" & Large Oval	U-Factor	0.29	0.26	0.29	0.26	0.27	0.24	0.24	0.30	0.26	0.25	0.25	0.26	0.23	0.23	0.23	0.28	0.28	0.24	0.24
	SHGC	0.23	0.19	0.21	0.17	0.23	0.19	0.17	0.23	0.19	0.07	0.17	0.19	0.18	0.15	0.14	0.20	0.18	0.19	0.17
	DT/VT	0.23	0.21	0.21	0.19	0.23	0.21	0.19	0.23	0.21	-	0.18	0.22	0.20	0.17	0.17	0.22	0.20	0.20	0.18
<b>Full Light</b> 64" & 80"	U-Factor	0.34	0.30	0.34	0.29	0.32	0.27	0.27	0.35	0.30	0.29	0.28	0.30	0.26	0.26	0.26	0.32	0.32	0.27	0.27
	SHGC	0.30	0.25	0.28	0.23	0.30	0.25	0.23	0.30	0.26	0.09	0.22	0.25	0.24	0.21	0.19	0.27	0.25	0.25	0.23
	DT/VT	0.31	0.28	0.28	0.25	0.31	0.28	0.25	0.31	0.29	-	0.24	0.30	0.27	0.23	0.23	0.30	0.27	0.28	0.25

- Half light doorglass must be equal to or less than .25/.25 for U factor & SHGC
- Doorglass larger than half lights must be .30/.40 in North or North Central regions
- Doorglass larger than half lights must be .30/.25 in South or South Central regions

**U-Factor:** Defines the amount of heat loss. The lower the value, the less heat is transmitted through the entry door.

**Solar Heat Gain Coefficient (SHGC):** The portion of directly transmitted and absorbed solar energy that enters the interior. The lower the value, the less heat is transmitted through the entry.

**Daylight Transmission/Visible Transmission (DT/VT):** Measures how much light comes through the entry. The higher the value, from 0 to 1, the more daylight is let in over the unit area of the entry.

The performance ratings above were developed by Architectural Testing using applicable NFRC procedures for determining whole product performance. The ratings are determined for a fixed set of conditions and specs.